

## PAKOWANIE, PARAMETRY TECH

nazwa produktu	wymiary płyty (mm)			ilość płyt/op	ilość m <sup>2</sup> /op	ilość m <sup>3</sup> /op	lambda (λ)	opór cieplny (Rd)
	grubość	szerokość	długość					
RAVATHERM XPS 250 PB	20	600	1250	20,00	15,00	0,300	0,033	0,600
RAVATHERM XPS 300 SL F	30	600	1250	14,00	10,50	0,315	0,033	0,900
RAVATHERM XPS 300 SL F	40	600	1250	10,00	7,50	0,300	0,033	1,200
RAVATHERM XPS 300 SL F	50	600	1250	8,00	6,00	0,300	0,033	1,500
RAVATHERM XPS 300 SL F	60	600	1250	7,00	5,25	0,315	0,033	1,800
RAVATHERM XPS 300 SL F	80	600	1250	5,00	3,75	0,300	0,033	2,400
RAVATHERM XPS 300 SL F	100	600	1250	4,00	3,00	0,300	0,034	2,900
RAVATHERM XPS 300 SL F	120	600	1250	3,00	2,25	0,270	0,034	3,500
RAVATHERM XPS 300 SL F	150	600	1250	2,00	1,50	0,225	0,035	4,250
RAVATHERM XPS 500SL F	40	600	1250	10,00	7,50	0,300	0,034	1,150
RAVATHERM XPS 500SL F	50	600	1250	8,00	6,00	0,300	0,034	1,450
RAVATHERM XPS 500SL F	60	600	1250	7,00	5,25	0,315	0,034	1,750
RAVATHERM XPS 500SL F	80	600	1250	5,00	3,75	0,300	0,034	2,350
RAVATHERM XPS 500SL F	100	600	1250	4,00	3,00	0,300	0,035	2,850
RAVATHERM XPS 500SL F	120	600	1250	3,00	2,25	0,270	0,035	3,400
RAVATHREM XPS 700SL F	40	600	1250	10,00	7,50	0,300	0,034	1,150
RAVATHREM XPS 700SL F	50	600	1250	8,00	6,00	0,300	0,034	1,450
RAVATHREM XPS 700SL F	60	600	1250	7,00	5,25	0,315	0,034	1,750
RAVATHREM XPS 700SL F	80	600	1250	5,00	3,75	0,300	0,034	2,350
RAVATHREM XPS 700SL F	100	600	1250	4,00	3,00	0,300	0,035	2,850