



## Declaration of performance

Nr 19/20/KA/2020

<b>1. Unique identification code of the product-type:</b>	KNAUF Therm Pro Fasada/Dach/Podłoga EPS 70 λ 38 d <sub>N</sub> 20 (TYP EPS 70) EPS-EN 13163-T(1)-L(2)-W(2)-S(2)-P(5)-BS115-CS(10)70-DS(N)2-DS(70,-) 11-TR100
<b>2. Intended use or uses:</b>	Thermal insulation for buildings
<b>3. Name, registered trade name or registered trade mark and contact address of the manufacturer:</b>	Knauf Industries Polska Sp. z o.o. Adamowice ul. Styropianowa 1, 96-320 Mszczonów
<b>4. Name and contract address of the authorized representative</b>	Not relevant
<b>5. System or systems of assessment and verification of constancy of performance of the construction product</b>	System 3
<b>6a. Harmonized standard:</b>	EN 13163:2012+A1:2015.
<b>Notified testing facility:</b>	Notified testing laboratory 1488 Building Research Institute
<b>6b. European Assessment Document</b>	Not relevant
<b>European Technical Assessment</b>	Not relevant
Technical assessment facility:	Not relevant
<b>Notified testing facility</b>	Not relevant

7. Declared performance:			
Essential Characteristics	Performance properties	Declared class/level/NDP <sup>a)</sup>	Harmonised technical specification
Thermal resistance	Thermal conductivity and resistance	R <sub>D</sub> - 0,50 m²K/W λ <sub>D</sub> - 0,038 W/mK	EN 13163:2012+A1:2015
	Thickness	T(1) d <sub>N</sub> -20 [mm]	
Reaction to fire	Reaction to fire	E	
Durability of reaction to fire - in function of heat, atmospheric conditions, aging/degradation	Properties Durability <sup>b)</sup>	E	
Durability of thermal resistance and thermal conductivity against aging/degradation	Thermal resistance and thermal conductivity <sup>c)</sup>	R <sub>D</sub> - 0,50 m²K/W λ <sub>D</sub> - 0,038 W/mK	
	Properties Durability	NPD	
Compressive strength	Compressive strength at 10% deformation CS (10) [kPa]	CS(10)70	
Tensile/Flexural strength	Bending strength BS [kPa]	BS 115	
	Tensile strength perpendicular to faces TR [kPa]	TR 100	
Durability of compressive strength against aging and degradation	Compressive creep CC [%]	NPD	
	Freeze-thaw resistance [%]	NPD	
	Long-term thickness reduction [mm]	NPD	
Water permability	Water permeability WL(T)	NPD	
	Water absorbtion WD(V)	NPD	
Vapor permability	Vapor permability [μ]	NPD	
Impact noise transmission index	Dynamic stiffness SD [MN/m³]	NPD	
	Thickness d <sub>L</sub> [mm]	NPD	
	Compressibility CP [mm]	NPD	
Continuous glowing combustion	Continuous glowing combustion <sup>d)</sup>	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances to the indoor environment <sup>d)</sup>	NPD	
<sup>a)</sup> <b>NPD</b> - No Performance declare; <sup>b)</sup> No change in reaction to fire properties for EPS products; <sup>c)</sup> Thermal resistance and thermal conductivity of EPS products don't change with time; <sup>d)</sup> Europe research is ongoing;			

## **8. Appropriate Technical Documentation or Specific Technical Documentation:**

Not applicable

**The performance of the product identified above is consistent with the set of declared performance.**

**This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.**

Signed for and on behalf of the manufacturer:

(name:) Paweł Zemlik

(place:) Adamowice

(date:) 1.07.2021

(signature:)

